

ChloraPrep[®] Solutions

Safety Data Sheet

according to Regulation (EC) No. 453/2010 Date of issue: 30/03/2015

SECTIO	ON 1: Identification of the su	ubstance/mixture and of the company/undertaking					
1.1.	Product identifier						
Product r	roduct name : ChloraPrep Solutions						
1.2.	Relevant identified uses of the substance or mixture and uses advised against						
1.2.1.	Relevant identified uses						
Use of th	e substance/mixture	: Antimicrobial					
1.2.2. No additi	Uses advised against onal information available						
Vernon H	Details of the supplier of the safet ion irway Drive fills, IL 60061 i3-0502 - F 855-329-6985	ty data sheet					
1.4.	Emergency telephone number						
Emergen	icy number	 For Hazardous Materials [or Dangerous Goods] Incident Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 CCN702157 Outside USA and Canada: +1 703-741-5970 (collect calls accepted) Within EU: +(44)-870-8200418 					

CHEMTREC UK (London): +(44)-870-8200418

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP] and GHS US

Flam. Liq. 2 H225 Eye Irrit. 2 H319 STOT SE 3 H336 STOT SE 3 H335

Full text of H-phrases: see section 16

Classification according to Directive 67/548/EEC or 1999/45/EC

F; R11 Xi; R36 R67 Full text of R-phrases: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labeling according to Regulation (EC) No. 1272/2008 [CLP] and GHS US

Hazard pictograms

	GHS02 GHS07
Signal word	: Danger
Hazard statements	: H225 - Highly flammable liquid and vapor H319 - Causes serious eye irritation H335 - May cause respiratory irritation H336 - May cause drowsiness or dizziness
Precautionary statements	: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
30/03/2015	EN (English LIS) 1/10

P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P241 - Use explosion-proof electrical/ventilating/lighting/ equipment
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray
P264 - Wash thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing.
Rinse skin with water/shower
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove
contact lenses, if present and easy to do. Continue rinsing
P312 - Call a POISON CENTER/doctor/ if you feel unwell
P337+P313 - If eye irritation persists: Get medical advice/attention
P370+P378 - In case of fire: Use to extinguish
P403+P233 - Store in a well-ventilated place. Keep container tightly closed
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P501 - Dispose of contents/container to

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

ര

Name	Product identifier	%	Classification according to Directive 67/548/EEC	Classification according to Regulation (EC) No. 1272/2008 [CLP]	GHS-US classification
Isopropyl alcohol	(CAS No) 67-63-0 (EC no) 200-661-7 (EC index no) 603-117-00-0	70	F; R11 Xi; R36 R67	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	Flam. Liq. 2, H225
Chlorhexidine digluconate	(CAS No) 18472-51-0 (EC no) 242-354-0	2	Not classified	Acute Tox. 4 (Oral), H302	Acute Tox. 4 (Oral), H302

ChloraPrep[®] Hi-Lite Orange

Name	Product identifier	%	Classification according to Directive 67/548/EEC	Classification according to Regulation (EC) No. 1272/2008 [CLP]	GHS-US classification
Isopropyl alcohol	(CAS No) 67-63-0 (EC no) 200-661-7 (EC index no) 603-117-00-0	70	F; R11 Xi; R36 R67	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	Flam. Liq. 2, H225
Chlorhexidine digluconate	(CAS No) 18472-51-0 (EC no) 242-354-0	2	Not classified	Acute Tox. 4 (Oral), H302	Acute Tox. 4 (Oral), H302
FD and C Yellow No. 6	(CAS No) 2783-94-0 (EC no) 220-491-7	0 - 0.1	Not classified	Not classified	Not classified

ChloraPrep[®] Teal Green

Name	Product identifier	%	Classification according to Directive 67/548/EEC	Classification according to Regulation (EC) No. 1272/2008 [CLP]	GHS-US classification
Isopropyl alcohol	(CAS No) 67-63-0 (EC no) 200-661-7 (EC index no) 603-117-00-0	70	F; R11 Xi; R36 R67	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	Flam. Liq. 2, H225
Chlorhexidine digluconate	(CAS No) 18472-51-0 (EC no) 242-354-0	2	Not classified	Acute Tox. 4 (Oral), H302	Acute Tox. 4 (Oral), H302
C.I. Food Green 3	(CAS No) 2353-45-9 (EC no) 219-091-5	0 - 0.1	Not classified	Muta. 2, H341	Muta. 2, H341

Full text of R- and H- phrases: see section 16

SECTION 4: First aid measures						
4.1. Description of first aid measures						
First-aid measures after inhalation	If symptoms of exposure develop, move to fresh air. Seek medical attention if symptoms persist.					
First-aid measures after skin contact	Wash material off the skin with copious amounts of water. If redness or a burning sensation develops, seek medical attention and discontinue use.					
First-aid measures after eye contact	Flush with copious amounts of water. After initial flushing remove any contact lenses and continue flushing for at least 15minutes. Have eyes examined and treated by medical personnel immediately.					
First-aid measures after ingestion	Give individual one to two glasses of water to drink. If gastrointestinal symptoms develop, consult medical personnel. (Never give anything by mouth to an unconscious person).					
4.2. Most important symptoms and effects	, both acute and delayed					
Symptoms/injuries after inhalation	Inhalation of vapors may cause mucous membrane and respiratory irritation and central nervous system depression with symptoms of headache, dizziness and drowsiness.					
Symptoms/injuries after skin contact	May cause irritation, drying, defatting of the skin. Prolonged contact may cause dermatitis.					
Symptoms/injuries after eye contact	Contact may cause severe irritation with redness, tearing and pain with possible eye damage.					
Symptoms/injuries after ingestion	Ingestion may cause mucous membrane and gastrointestinal irritation, abdominal pain, nausea, vomiting, dizziness and drowsiness.					
4.3. Indication of any immediate medical a	4.3. Indication of any immediate medical attention and special treatment needed					
No additional information available						
SECTION 5: Firefighting measures						

SECTION 5. Filengining measures				
5.1.	Extinguishing media			
Suitable extinguishing media		:	Water fog, alcohol-resistant foam, carbon dioxide or dry chemical. Water spray can be used to cool exposed containers and structures, dilute spills and disperse flammable vapors.	
Unsuitab	le extinguishing media	:	None.	
5.2.	5.2. Special hazards arising from the substance or mixture			
Fire hazard		:	Highly flammable liquid and vapor. Ampoules may explode if exposed to extreme heat or flame. Vapors are heavier than air and will travel along surfaces to remote ignition sources and flash back.	
Explosion hazard		:	None known.	
5.3. Advice for firefighters				
Protection during firefighting		:	Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing.	

SECTIO	SECTION 6: Accidental release measures						
6.1.	Personal precautions, protective equipment and emergency procedures						
General measures			No special measures required.				
6.1.1.	For non-emergency personnel						
No addition	onal information available						
6.1.2.	For emergency responders						
No addition	onal information available						
6.2.	Environmental precautions						
Avoid rele	ease to the environment.						
6.3.	Methods and material for containmen	nt a	and cleaning up				
For conta	inment	:	Stop the flow of material, if this is without risk.				
Methods for cleaning up		:	Wear skin, eye and respiratory protection during cleanup.For small spills, wipe or mop up and rinse to sewer serviced by a wastewater treatment facility. For large spills, eliminate sources of ignition and ventilate spill area. Soak up liquid with inert absorbent and collect into a suitable waste container. Wash residue from spill area with water and flush to sewer serviced by a wastewater treatment facility if permitted.				
6.4.	Reference to other sections						
No additi	onal information available						
SECTIO	ON 7: Handling and storage						
7.1.	Precautions for safe handling						
Precautio	ns for safe handling	:	Avoid prolonged exposure (ingestion, inhalation, or skin contact). Avoid breathing vapors. Use in well-ventilated areas. Keep product away from heat, sparks and flames.				
7.2.	Conditions for safe storage, including	ga	any incompatibilities				
Storage conditions		:	Store in a cool, dry, well-ventilated area away from incompatible chemicals and all sources of ignition.				

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. **Control parameters**

Isopropyl alcohol (67-6		
Austria	MAK (mg/m³)	500 mg/m ³ (short time value for large casting)
Austria Austria	MAK (ppm) MAK Short time value (mg/m³)	200 ppm (short time value for large casting) 2000 mg/m ³ 2000 mg/m ³ (STEL for large casting valid till 12/31/2013)
Austria	MAK Short time value (ppm)	800 ppm 800 ppm (STEL for large casting valid till 12/31/2013)
Belgium	Limit value (mg/m ³)	500 mg/m ³
Belgium	Limit value (ppm)	200 ppm
Belgium	Short time value (mg/m ³)	1000 mg/m ³
Belgium	Short time value (ppm)	400 ppm
Bulgaria	OEL TWA (mg/m ³)	980.0 mg/m ³
Bulgaria	OEL STEL (mg/m ³)	1225.0 mg/m ³
Croatia	GVI (granična vrijednost izloženosti) (mg/m ³)	999 mg/m ³
Croatia	GVI (granična vrijednost izloženosti) (ppm)	400 ppm
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (mg/m ³)	1250 mg/m ³
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (ppm)	500 ppm
Czech Republic	Exposure limits (PEL) (mg/m ³)	500 mg/m ³
Denmark	Limit (long-term) (mg/m ³)	490 mg/m ³
Denmark	Limit (long-term) (ppm)	200 ppm
Estonia	OEL TWA (mg/m³)	350 mg/m ³
Estonia	OEL TWA (ppm)	150 ppm
Estonia	OEL STEL (mg/m ³)	600 mg/m ³
Estonia	OEL STEL (ppm)	250 ppm
Finland	HTP-arvo (8h) (mg/m ³)	500 mg/m ³
Finland	HTP-arvo (8h) (ppm)	200 ppm
Finland	HTP-arvo (15 min)	620 mg/m ³
Finland	HTP-arvo (15 min) (ppm)	250 ppm
France	VLE (mg/m ³)	980 mg/m ³
France	VLE (ppm)	400 ppm
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	500 mg/m ³ (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Germany	TRGS 900 Occupational exposure limit value (ppm)	200 ppm (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Germany	TRGS 903 (BGW)	25 mg/l (Medium: whole blood - Time: end of shift - Parameter: Acetone) 25 mg/l (Medium: urine - Time: end of shift - Parameter: Acetone)
Greece	OEL TWA (mg/m ³)	980 mg/m ³
Greece	OEL TWA (ppm)	400 ppm
Greece	OEL STEL (mg/m ³)	1225 mg/m ³
Greece	OEL STEL (ppm)	500 ppm
Hungary	Exposure Limit Value	500 mg/m ³
Hungary	CK-érték	2000 mg/m ³
Ireland	OEL (8 hours ref) (ppm)	200 ppm
Ireland	OEL (15 min ref) (ppm)	400 ppm
Latvia	OEL TWA (mg/m³)	350 mg/m ³
Lithuania	IPRV (mg/m ³)	350 mg/m ³
Lithuania	IPRV (ppm)	150 ppm
0/03/2015	EN (English US)	4/1

Isopropyl alcohol (67-6	3-0)	
Lithuania	TPRV (mg/m ³)	600 mg/m³
Lithuania	TPRV (ppm)	250 ppm
Poland	NDS (mg/m ³)	900 mg/m ³
Poland	NDSCh (mg/m ³)	1200 mg/m ³
	())	ÿ
Portugal	OEL TWA (ppm) OEL STEL (ppm)	200 ppm 400 ppm
Portugal Romania	OEL TWA (mg/m ³)	200 mg/m ³
Romania	OEL TWA (ng/m ²) OEL TWA (ppm)	81 ppm
Romania	OEL STEL (mg/m ³)	500 mg/m ³
Romania	OEL STEL (ppm)	203 ppm
Slovakia	NPHV (priemerná) (mg/m ³)	500 mg/m ³
Slovakia	NPHV (priemerná) (ppm)	200 ppm
	. , ,	
Slovakia	NPHV (Hraničná) (mg/m ³)	1000 mg/m ³
Slovenia	OEL TWA (mg/m ³)	500 mg/m ³
Slovenia	OEL TWA (ppm)	200 ppm
Slovenia	OEL STEL (mg/m ³)	2000 mg/m ³
Slovenia	OEL STEL (ppm)	800 ppm
Spain	VLA-ED (mg/m ³)	500 mg/m ³ (it is prohibited the partial or complete commercialization or use of this substance as a phytosanitary or biocide compound)
Spain	VLA-ED (ppm)	200 ppm (it is prohibited the partial or complete commercialization or use of this substance as a phytosanitary or biocide compound)
Spain	VLA-EC (mg/m ³)	1000 mg/m ³
Spain	VLA-EC (ppm)	400 ppm
Sweden	nivågränsvärde (NVG) (mg/m ³)	350 mg/m ³
Sweden	nivågränsvärde (NVG) (ppm)	150 ppm
Sweden	kortidsvärde (KTV) (mg/m ³)	600 mg/m ³
Sweden		
	kortidsvärde (KTV) (ppm)	250 ppm
United Kingdom	WEL TWA (mg/m³)	999 mg/m ³
United Kingdom United Kingdom	WEL TWA (ppm) WEL STEL (mg/m ³)	400 ppm 1250 mg/m ³
United Kingdom	WEL STEL (mg/m ^s) WEL STEL (ppm)	500 ppm
Norway	TWA (AN) (mg/m ³)	245 mg/m ³
Norway	TWA (AN) (ppm)	100 ppm
Norway	TWA (Korttidsverdi) (mg/m3)	306.25 mg/m ³
Norway	TWA (Korttidsverdi) (ppm)	150 ppm
Switzerland	VME (mg/m ³)	500 mg/m³
Switzerland	VME (ppm)	200 ppm
Switzerland	VLE (mg/m ³)	1000 mg/m ³
Switzerland	VLE (ppm)	400 ppm
Australia	TWA (mg/m ³)	983 mg/m ³
Australia	TWA (ppm)	400 ppm
Australia	STEL (mg/m ³)	1230 mg/m ³
Australia	STEL (ppm) VECD (mg/m ³)	500 ppm
Canada (Quebec)		1230 mg/m ³
Canada (Quebec) Canada (Quebec)	VECD (ppm) VEMP (mg/m ³)	500 ppm 985 mg/m ³
Canada (Quebec)	VEMP (ppm)	400 ppm
USA - ACGIH	ACGIH TWA (ppm)	200 ppm
USA - ACGIH	ACGIH STEL (ppm)	400 ppm
USA - IDLH	US IDLH (ppm)	2000 ppm (10% LEL)
USA - NIOSH	NIOSH REL (TWA) (mg/m ³)	980 mg/m ³
USA - NIOSH	NIOSH REL (TWA) (ppm)	400 ppm
	, , , , , , ,	
USA - NIOSH	NIOSH REL (STEL) (mg/m ³)	1225 mg/m ³
30/03/2015	EN (English US)	5/10

ChloraPrep® Solutions

Safety Data Sheet

Isopropyl alcohol (67-63-0)		
USA - NIOSH	NIOSH REL (STEL) (ppm)	500 ppm
USA - OSHA	OSHA PEL (TWA) (mg/m ³)	980 mg/m³
USA - OSHA	OSHA PEL (TWA) (ppm)	400 ppm

8.2. Exposure controls

Appropriate engineering controls	Use with adequate general or local exhaust ventilation to maintain exposures below the occupational exposure limits. Use explosion proof equipment where required.	
Hand protection	Latex rubber for limited contact. Butyl rubber or nitrile recommended for prolonged contact.	
Eye protection	Safety glasses or goggles recommended if eye contact is possible.	
Skin and body protection	Wear suitable working clothes.	
Respiratory protection	If the exposure limits are exceeded a NIOSH/EN approved organic vapor respirator appropria for the form and concentration of the contaminants should be used.	ate

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and	chemical properties
Physical state	: Liquid
Appearance	: Clear in product; when activated, clear orange, teal
Color	: Clear, orange, or teal
Odor	: Odourless
Odor threshold	: No data available
рН	: 7-7.5
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 19.4°C (67 °F)
Auto-ignition temperature	: 2 - 12.7
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: 0.88
Solubility	: Water: Complete
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosive limits	: No data available
9.2. Other information	
VOC content	: 100 %

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions Will not occur.

10.4. Conditions to avoid

Extreme heat, sparks or flame.

10.5. Incompatible materials

Oxidizing materials

10.6. Hazardous decomposition products

Carbon dioxide, carbon monoxide, nitrogen oxides, ammonia, chlorine compounds.

ChloraPrep[®] Solutions

Safety Data Sheet

SECTION 11: Toxicological information		
11.1. Information on toxicological effects		
Acute toxicity	: Not classified	
Isopropyl alcohol (67-63-0)		
LD50 oral rat	4396 mg/kg	
LD50 dermal rabbit	12800 mg/kg	
LC50 inhalation rat (ppm)	16000 ppm (Exposure time: 8 h)	
Chlorhexidine digluconate (18472-51-0)		
ATE (oral)	500.000 mg/kg	
Skin corrosion/irritation	: Not classified	
Serious eye damage/irritation	: Causes serious eye irritation.	
Respiratory or skin sensitization	: Not classified	
Germ cell mutagenicity	: Not classified	
Carcinogenicity	: Not classified	
Isopropyl alcohol (67-63-0)		
IARC group	3 - Not classifiable	
C.I. Food Green 3 (2353-45-9)		
IARC group	3 - Not classifiable	
FD and C Yellow No. 6 (2783-94-0)		
IARC group	3 - Not classifiable	
Reproductive toxicity	: Not classified	
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness. May cause respiratory irritation.	
Specific target organ toxicity (repeated exposure)	: Not classified	
Aspiration hazard	: Not classified	

SECTION 12:	Ecologica	l information

12.1. Toxicity

Isopropyl alcohol (67-63-0)		
LC50 fishes 1	9640 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])	
EC50 Daphnia 1	13299 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
EC50 other aquatic organisms 1	> 1000 mg/l (Exposure time: 96 h - Species: Desmodesmus subspicatus)	
LC50 fish 2	11130 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])	
EC50 other aquatic organisms 2	> 1000 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)	

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Isopropyl alcohol (67-63-0)	
Log Pow	0.05 (at 25 °C)
12.4. Mobility in soil	

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

13.1. Waste treatment methods

Waste disposal recommendations

: Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / AND / US DOT

Safety Data Sheet	
14.1. UN number	
UN-No.	: 1219
14.2. UN proper shipping name	
Proper Shipping Name	: ISOPROPANOL (ISOPROPYL ALCOHOL)
14.3. Transport hazard class(es)	
Transport hazard class(es)	: 3
Danger labels	: 3
	3
	•
14.4. Packing group	
Packing group	: 11
14.5. Environmental hazards	
Dangerous for the environment	: No
Marine pollutant	: No
Other information	: No supplementary information available
14.6. Special precautions for user	
14.6.1. Overland transport	
Classification code (ADR)	: F1
Special provision (ADR)	: 601
Limited quantities (ADR)	: 1L
Excepted quantities (ADR)	: E2
Packing instructions (ADR)	: P001, IBC02, R001
Mixed packing provisions (ADR)	: MP19
Mixed Portable tank and bulk container instructions (ADR)	: T4
Mixed Portable tank and bulk container specia	al : TP1
provisions (ADR)	
ADR tank codes (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 2
Special provisions for carriage - Operation : S2, S20 (ADR)	
Hazard identification number (Kemler No.)	: 33
Orange plates	22
	33
	1219
Tunnel restriction code (ADR)	: D/E
EAC	: •2YE

14.6.2. Transport by sea

14.6.3. Air transport

14.6.4. Inland waterway transport Not subjected to ADN

14.6.5. Rail transport Carriage prohibited (RID)

: No

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable

: No

SECTION 15: Regulatory informa	tion
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture	
15.1.1. EU-Regulations	
Contains no substances with Annex XVII res	trictions
Contains no REACH candidate substance	suctions
Contains no REACH Annex XIV substances	
	•
VOC content	: 100 %
15.1.2. National regulations	
Germany	
Water hazard class (WGK)	: 2 - hazardous to water
15.2 Chemical safety assessment	
· · · · · · · · · · · · · · · · · · ·	
No additional information available	
No additional information available	
15.2.Chemical safety assessmentNo additional information available15.3. US Federal regulationsIsopropyl alcohol (67-63-0)	
No additional information available 15.3. US Federal regulations Isopropyl alcohol (67-63-0) Listed on the United States TSCA (Toxic S	
No additional information available 15.3. US Federal regulations Isopropyl alcohol (67-63-0) Listed on the United States TSCA (Toxic S Listed on SARA Section 313 (Specific toxic	c chemical listings)
No additional information available 15.3. US Federal regulations Isopropyl alcohol (67-63-0) Listed on the United States TSCA (Toxic S Listed on SARA Section 313 (Specific toxic EPA TSCA Regulatory Flag	c chemical listings) T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
No additional information available 15.3. US Federal regulations Isopropyl alcohol (67-63-0) Listed on the United States TSCA (Toxic S Listed on SARA Section 313 (Specific toxic	c chemical listings)
No additional information available 15.3. US Federal regulations Isopropyl alcohol (67-63-0) Listed on the United States TSCA (Toxic S Listed on SARA Section 313 (Specific toxic EPA TSCA Regulatory Flag	c chemical listings) T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
No additional information available 15.3. US Federal regulations Isopropyl alcohol (67-63-0) Listed on the United States TSCA (Toxic S Listed on SARA Section 313 (Specific toxic EPA TSCA Regulatory Flag SARA Section 313 - Emission Reporting	c chemical listings) T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA. 1.0 % (only if manufactured by the strong acid process, no supplier notification)
No additional information available 15.3. US Federal regulations Isopropyl alcohol (67-63-0) Listed on the United States TSCA (Toxic S Listed on SARA Section 313 (Specific toxic EPA TSCA Regulatory Flag SARA Section 313 - Emission Reporting C.I. Food Green 3 (2353-45-9) Listed on the United States TSCA (Toxic S	c chemical listings) T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA. 1.0 % (only if manufactured by the strong acid process, no supplier notification)
No additional information available 15.3. US Federal regulations Isopropyl alcohol (67-63-0) Listed on the United States TSCA (Toxic S Listed on SARA Section 313 (Specific toxic EPA TSCA Regulatory Flag SARA Section 313 - Emission Reporting C.I. Food Green 3 (2353-45-9)	c chemical listings) T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA. 1.0 % (only if manufactured by the strong acid process, no supplier notification) Substances Control Act) inventory
No additional information available 15.3. US Federal regulations Isopropyl alcohol (67-63-0) Listed on the United States TSCA (Toxic S Listed on SARA Section 313 (Specific toxid EPA TSCA Regulatory Flag SARA Section 313 - Emission Reporting C.I. Food Green 3 (2353-45-9) Listed on the United States TSCA (Toxic S Chlorhexidine digluconate (18472-51-0)	c chemical listings) T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA. 1.0 % (only if manufactured by the strong acid process, no supplier notification) Substances Control Act) inventory

15.4. US State regulations

Isopropyl alcohol (67-63-0)

U.S. - Massachusetts - Right To Know List

U.S. - Minnesota - Hazardous Substance List

U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Full text of R-, H- and EUH-phrases:

Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Eye Irrit. 2	Serious eye damage/eye irritation Category 2
Flam. Liq. 2	Flammable liquids Category 2
Muta. 2	Germ cell mutagenicity Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapour
H302	Harmful if swallowed
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H341	Suspected of causing genetic defects
R11	Highly flammable
R36	Irritating to eyes
R67	Vapors may cause drowsiness and dizziness
F	Highly flammable
Xi	Irritant

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product